



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

4-4700: R1200 Red Urethane

Color: Red

Plies: 1

Nom. OAG: 0.187" +/- 0.02"

Fabric: Interwoven Polyester

Top Surface: Urethane

Bottom Surface: Friction Surface

Compound: Poly Urethane

Work Tension: 120 lbs./PIW

Elongation: Less than 2%

Weight: 0.1 lbs./PIW

Minimum Pulley: 4"

Backflex Min. Pulley Dia.: 6"

Working Temp. (F): 0 to 185

Max. Stocked Width: 72"

Attributes: Sliderbed Suitable, Abrasion Resistant

Hardness: 85a

Top Cover Coefficient of Friction: 0.85

Bottom Cover Coefficient of Friction: 0.25

Features: This is one of the toughest, most abrasive belts on the market. The 3/32" thick, 85 Durometer urethane cover will resist cutting and abrasion from metal, glass, aluminum and other abrasive materials. R1200 Urethane-Novex is used in metal stamping, recycling, die cutting and brick manufacturing applications.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39