



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

4-4701: R1200 Red URA-Stamp

Color: Red

Plies: 1

Nom. OAG: 0.22" +/- 0.015"

Fabric: Interwoven Polyester

Top Surface: Smooth Urethane

Bottom Surface: Friction Surface

Compound: Poly Urethane

Work Tension: 120 lbs./PIW

Elongation: Less than 2%

Weight: 0.108 lbs./PIW

Minimum Pulley: 3"

Backflex Min. Pulley Dia.: 4.5"

Working Temp. (F): 20 to 180

Max. Stocked Width: 72"

Attributes: Sliderbed Suitable, Abrasion Resistant

Top Cover Coefficient of Friction: 0.4

Bottom Cover Coefficient of Friction: 0.3

Features: 4-4701 is one of the toughest, most abrasion resistant belts on the market. The 2mm thick cover will resist cutting and abrasion from metal, glass, aluminum and other abrasive materials. This belt has good resistance to oil. Red URA-Stamp is used in metal stamping, recycling, die cutting, brick manufacture and any other high abrasion application.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39