



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 5-1502: 2 Ply 150 1/8 X Bare MOR

**Color:** Black

**Plies:** 2

**Nom. OAG:** 0.22" +/- 0.03"

**Fabric:** Polyester/Nylon

**Top Surface:** Smooth Cover

**Top Cover Thickness:** 0.125"

**Bottom Surface:** Bare

**Compound:** MOR

**Work Tension:** 150 lbs./PIW

**Elongation:** Less than 3%

**Weight:** 0.11 lbs./PIW

**Minimum Pulley:** 6"

**Backflex Min. Pulley Dia.:** 9"

**Working Temp. (F):** -20 to 225

**Max. Stocked Width:** 84"

**Attributes:** Sliderbed Suitable,  
Troughable

**Hardness:** 65a

**Features:** 5-1502 features a medium duty, abrasion resistant top cover on a bare bottom cover. This belt can be used on a slider bed and is moderately oil resistant. 150 1/8 x Bare MOR can be used in any application requiring a medium duty belt on a slider bed. It is an excellent belt for recycling applications, the glass industry and processing wood chips, paper and scrap.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39