



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-2335: 2 Ply 220 1/16 x 1/16 M-MOR-SC

Color: Black

Plies: 2

Nom. OAG: 0.215" +/- 0.03"

Fabric: Polyester/Nylon

Top Surface: Smooth Cover

Top Cover Thickness: 0.0625"

Bottom Surface: Smooth Cover

Bottom Cover Thickness: 0.0625"

Compound: SCORF

Work Tension: 220 lbs./PIW

Elongation: Less than 4%

Weight: 0.136 lbs./PIW

Working Temp. (F): 0 to 250

Max. Stocked Width: 72"

Attributes: Fire Retardant, Static
Conductive to $< 3 \times 10^8$ ohms, OSHA 29
CFR, Oil Resistant, Troughable

Hardness: 65a

Minimum Pulley Chart:

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

Features: 5-2335 is static conductive, moderately oil resistant, fire retardant and MSHA approved for grain elevators. This belt is not approved for use in underground applications. 220 1/16 X 1/16 M-MOR-SC is an excellent belt for bucket elevator applications. Mulhern Belting can punch a wide variety of patterns for any bucket configuration in this belt. It is also ideal to convey oily grains or wood chips.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39