



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-2442: 4 Ply 220 1/8 x 1/16 CR-MOR

Color: Black

Plies: 4

Nom. OAG: 0.46" +/- 0.03"

Fabric: Polyester/Monofilament

Top Surface: Smooth Cover

Top Cover Thickness: 0.125"

Bottom Surface: Smooth Cover

Bottom Cover Thickness: 0.0625"

Compound: MOR

Work Tension: 220 lbs./PIW

Elongation: Less than 4%

Weight: 0.23 lbs./PIW

Working Temp. (F): -20 to 225

Max. Stocked Width: 60"

Attributes: Cross Rigid, Oil Resistant

Hardness: 65a

Minimum Pulley Chart:

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

Features: 5-2442 offers the same benefits as the 220 1/8" x 1/16" MOR with two traditional plies, but includes two additional monofilament plies for enhanced cross rigidity.. It is primarily used for sidewall belt fabrication and is not suitable for troughing applications. The 220 1/8" x 1/16" CR-MOR is a popular base belt for sidewall systems due to its cross-rigid construction.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39