



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-2502: 2 Ply 220 1/8 x Bare MOR

Color: Black

Plies: 2

Nom. OAG: 0.219" +/- 0.02"

Fabric: Polyester

Top Surface: Smooth Cover

Top Cover Thickness: 0.125"

Bottom Surface: Bare

Compound: MOR

Work Tension: 220 lbs./PIW

Elongation: Less than 4%

Weight: 0.125 lbs./PIW

Working Temp. (F): -20 to 225

Max. Stocked Width: 72"

Attributes: Sliderbed Suitable,
Troughable, Oil Resistant

Hardness: 65a

Minimum Pulley Chart:

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

Features: This belt features an abrasion resistant top cover and hefty carcass that will withstand high impact and still retain lacing. It is also moderately oil resistant. 220 1/8 x Bare MOR is popular in the lumber industry and anywhere an abrasion resistant cover is needed with a friction bottom surface. It is also moderately oil resistant.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39