



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-2531: 2 Ply 220 1/8 x 1/16 STD

Color: Black

Plies: 2

Nom. OAG: 0.3" +/- 0.03"

Fabric: Polyester/Nylon

Top Surface: Smooth Cover

Top Cover Thickness: 0.125"

Bottom Surface: Smooth Cover

Bottom Cover Thickness: 0.0625"

Compound: SBR

Work Tension: 220 lbs./PIW

Elongation: Less than 4%

Weight: 0.153 lbs./PIW

Working Temp. (F): -20 to 250

Max. Stocked Width: 84"

Attributes: Troughable

Hardness: 65a

Minimum Pulley Chart:

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

Features: 5-2531 features a smooth top and bottom surface. The heavy cover and high strength synthetic fabric results in a long wearing, mildew and rot resistant, low stretch belt. 220 1/8 X 1/16 STD is excellent for high abrasion applications. It is popular in the sand, gravel and rock industries as well as other heavy industrial applications.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39