



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-2702: 2 Ply 220 3/16 x Bare MOR

Color: Black

Plies: 2

Nom. OAG: 0.3" +/- 0.03"

Fabric: Polyester/Nylon

Top Surface: Smooth Cover

Top Cover Thickness: 0.1875"

Bottom Surface: Bare

Compound: MOR

Work Tension: 220 lbs./PIW

Weight: 0.165 lbs./PIW

Working Temp. (F): -20 to 225

Max. Stocked Width: 118.11"

Attributes: Sliderbed Suitable,
Troughable, Oil Resistant

Hardness: 65a

Minimum Pulley Chart:

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

Features: 5-2702 features a heavy duty, abrasion resistant top cover on a bare bottom cover. This belt can be used on a slider bed and is moderately oil resistant. 220 3/16" x Bare MOR can be used in any application requiring a heavy duty belt on a slider bed. It is an excellent belt for recycling applications and the glass industry.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39