



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-2732: 2 Ply 220 1/8 x 1/16 MOR

Color: Black

Plies: 2

Nom. OAG: 0.3" +/- 0.03"

Fabric: Polyester/Nylon

Top Surface: Smooth Cover

Top Cover Thickness: 0.125"

Bottom Surface: Smooth Cover

Bottom Cover Thickness: 0.0625"

Compound: MOR

Work Tension: 220 lbs./PIW

Elongation: Less than 4%

Weight: 0.153 lbs./PIW

Working Temp. (F): -20 to 225

Max. Stocked Width: 84"

Attributes: Oil Resistant, Troughable

Hardness: 65a

Minimum Pulley Chart:

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

Features: 5-2732 features the same qualities of the 220 3/16 x 1/16 STD except that it is Moderately Oil Resistant (MOR). 220 1/8 x 1/16 MOR is used to convey oily grain and wood chips. It is popular in sewage treatment where moderate oil is a problem.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39