



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-2733-MHT: 2 Ply 220 3/16 x 1/16 Maximum HT

Color: Black

Plies: 2

Nom. OAG: 0.36" +/- 0.03"

Fabric: Polyester/Nylon

Top Surface: Smooth Cover

Top Cover Thickness: 0.1875"

Bottom Surface: Smooth Cover

Bottom Cover Thickness: 0.0625"

Compound: EPM

Work Tension: 220 lbs./PIW

Elongation: Less than 4%

Weight: 0.2 lbs./PIW

Working Temp. (F): -20 to 700

Max. Stocked Width: 72"

Attributes: Heat Resistant

Hardness: 65a

Minimum Pulley Chart:

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

Features: 5-2733-MHT features a wide temperature range, with a high temperature approximately up to 400F (fines) and 700F (lumps). When used in it's recommended service range it resists hardening and cracking. It is also highly ozone resistant. The product is also known as the 700 Degree belt. 220 3/16 x 1/16 Maximum High Temp is used in many high heat, high abrasion applications---such as a foundry.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39