



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 5-2733: 2 Ply 220 3/16 x 1/16 HT

**Color:** Black

**Plies:** 2

**Nom. OAG:** 0.36" +/- 0.03"

**Fabric:** Polyester/Nylon

**Top Surface:** Smooth Cover

**Top Cover Thickness:** 0.1875"

**Bottom Surface:** Smooth Cover

**Bottom Cover Thickness:** 0.0625"

**Compound:** EPDM

**Work Tension:** 220 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.2 lbs./PIW

**Working Temp. (F):** -20 to 400

**Max. Stocked Width:** 72"

**Attributes:** Heat Resistant, Troughable

**Hardness:** 65a

**Minimum Pulley Chart:**

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

**Features:** 5-2733 features a wide temperature range, with a high temperature up to 350F (fines) and 400F (lumps). When used in it's recommended service range it resists hardening and cracking. It is also highly ozone resistant. 220 3/16 x 1/16 HT is used in many high heat, high abrasion applications---such as a foundry.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39