



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 5-2734-SOR: 2 Ply 220 3/16 x 1/16 Hot Asphalt SOR

**Color:** Black

**Plies:** 2

**Nom. OAG:** 0.36" +/- 0.03"

**Fabric:** Polyester/Nylon

**Top Surface:** Smooth Cover

**Top Cover Thickness:** 0.1875"

**Bottom Surface:** Smooth Cover

**Bottom Cover Thickness:** 0.0625"

**Compound:** SOR

**Work Tension:** 220 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.2 lbs./PIW

**Working Temp. (F):** -20 to 350

**Max. Stocked Width:** 72"

**Attributes:** Oil Resistance ASTM D471  
70C/72hrs/IRM903 < 10% Swell,  
Troughable, Oil Resistant

**Hardness:** 65a

**Minimum Pulley Chart:**

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

**Features:** 5-2734-SOR features a compound designed to service a combination of high temperature and oil. It has good abrasion resistance and retains flexibility in environments up to 350F in many applications. 220 3/16 x 1/16 SOR is popular carrying hot asphalt, oily grains and oil treated coal. It is also used in sewage treatment where oil can be a problem.

