



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 5-3442: 5 Ply 330 3/16 x 1/16 CR-MOR

**Color:** Black

**Plies:** 5

**Nom. OAG:** 0.535" +/- 0.03"

**Fabric:** Polyester/Nylon

**Top Surface:** Smooth Cover

**Top Cover Thickness:** 0.1875"

**Bottom Surface:** Smooth Cover

**Bottom Cover Thickness:** 0.0625"

**Compound:** MOR

**Work Tension:** 330 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.25 lbs./PIW

**Working Temp. (F):** -20 to 225

**Max. Stocked Width:** 72"

**Attributes:** Cross Rigid, Oil Resistant

**Hardness:** 65a

**Minimum Pulley Chart:**

Tension Rating	Min. Pulley Dia.
Over 80%	18"
60%-80%	16"
40%-60%	14"
Below 40%, tails, snubs	12"

**Features:** 5-3442 offers the same benefits as the 330 3/16" x 1/16" MOR with three traditional plies, but includes two additional monofilament plies for enhanced cross rigidity. It is specifically designed for sidewall belt fabrication and should not be used in troughing applications. The 330 3/16" x 1/16" CR-MOR is a popular choice as a base belt for sidewall systems due to its excellent cross-rigid properties.

