



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-3532: 3 Ply 330 3/16 x 1/16 MOR

Color: Black

Plies: 3

Nom. OAG: 0.41" +/- 0.03"

Fabric: Polyester/Nylon

Top Surface: Smooth Cover

Top Cover Thickness: 0.1875"

Bottom Surface: Smooth Cover

Bottom Cover Thickness: 0.0625"

Compound: MOR

Work Tension: 330 lbs./PIW

Elongation: Less than 4%

Weight: 0.217 lbs./PIW

Working Temp. (F): -20 to 225

Max. Stocked Width: 84"

Attributes: Oil Resistant, Troughable

Hardness: 65a

Minimum Pulley Chart:

| Tension Rating | Min. Pulley Dia. |
|-------------------------|------------------|
| Over 80% | 18" |
| 60%-80% | 16" |
| 40%-60% | 14" |
| Below 40%, tails, snubs | 12" |

Features: 5-3532 features the same qualities of the 330 3/16 x 1/16 STD except that it is Moderately Oil Resistant (MOR). 330 3/16 x 1/16 MOR is used to convey oily grain and wood chips. It is popular in sewage treatment where moderate oil is a problem.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39