



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 5-3635: 3 Ply 600 1/16 x 1/16 M-MOR-SC

**Color:** Black

**Plies:** 3

**Nom. OAG:** 0.36" +/- 0.03"

**Fabric:** Polyester/Nylon

**Top Surface:** Smooth Cover

**Top Cover Thickness:** 0.0625"

**Bottom Surface:** Smooth Cover

**Bottom Cover Thickness:** 0.0625"

**Compound:** SCORF

**Work Tension:** 600 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.193 lbs./PIW

**Minimum Pulley:** 18"

**Working Temp. (F):** 0 to 250

**Max. Stocked Width:** 60"

**Attributes:** Troughable, Static

Conductive to  $< 3 \times 10^8$  ohms, OSHA 29

CFR, Oil Resistant, Fire Retardant

**Hardness:** 65a

**Features:** Mulhern Belting's 5-3635 is static conductive, moderately oil resistant, fire retardant and MSHA approved for grain elevators. It is excellent for bucket elevator applications and conveying oily grains and wood chips. Mulhern Belting can punch a wide variety of patterns for any bucket configuration.

