



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 5-3702: 3 Ply 330 3/16 x Bare MOR

**Color:** Black

**Plies:** 3

**Nom. OAG:** 0.35" +/- 0.03"

**Fabric:** Polyester/Nylon

**Top Surface:** Smooth Cover

**Top Cover Thickness:** 0.1875"

**Bottom Surface:** Bare

**Compound:** MOR

**Work Tension:** 330 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.175 lbs./PIW

**Working Temp. (F):** -20 to 225

**Max. Stocked Width:** 96"

**Attributes:** Oil Resistant, Sliderbed  
Suitable, Troughable

**Hardness:** 65a

### Minimum Pulley Chart:

Tension Rating	Min. Pulley Dia.
Over 80%	18"
60%-80%	16"
40%-60%	14"
Below 40%, tails, snubs	12"

**Features:** 5-3702 features a heavy duty, abrasion resistant top cover on a bare bottom cover. This belt can be used on a slider bed and is moderately oil resistant. 330 3/16" x Bare MOR can be used in any application requiring a heavy duty belt on a slider bed. It is an excellent belt for recycling applications and the glass industry.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39