



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-3733: 3 Ply 330 3/16 x 1/16 HT

Color: Black

Plies: 3

Nom. OAG: 0.41" +/- 0.03"

Fabric: Polyester/Nylon

Top Surface: Smooth Cover

Top Cover Thickness: 0.1875"

Bottom Surface: Smooth Cover

Bottom Cover Thickness: 0.0625"

Compound: EPDM

Work Tension: 330 lbs./PIW

Elongation: Less than 4%

Weight: 0.217 lbs./PIW

Working Temp. (F): -20 to 400

Max. Stocked Width: 72"

Attributes: Heat Resistant, Troughable

Hardness: 65a

Minimum Pulley Chart:

Tension Rating	Min. Pulley Dia.
Over 80%	18"
60%-80%	16"
40%-60%	14"
Below 40%, tails, snubs	12"

Features: 5-3733 features a wide temperature range, with a high temperature up to 350F (fines) and 400F (lumps). When used in it's recommended service range it resists hardening and cracking. It is also highly ozone resistant. 330 3/16 x 1/16 HT is used in many high heat, high abrasion applications---such as a foundry.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39