



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 5-3734: 3 Ply 330 3/16 X 1/16 Hot Asphalt

**Color:** Black

**Plies:** 3

**Nom. OAG:** 0.41" +/- 0.03"

**Fabric:** Polyester/Nylon

**Top Surface:** Smooth Cover

**Bottom Surface:** Smooth Cover

**Compound:** SOR

**Work Tension:** 330 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.217 lbs./PIW

**Minimum Pulley:** 12"

**Working Temp:** -20 to 350 °F

**Max. Stocked Width:** 72"

**Attributes:** Oil Resistance ASTM D471

70C/72hrs/IRM903 < 20% Swell, Troughable, Oil Resistant

**Hardness:** 65a

**Top Cover Thickness:** 0.188"

**Bottom Cover Thickness:** 0.063"

### Features

5-3734 is formulated for applications requiring both heat resistance and moderate oil resistance. The compound remains flexible up to 350°F and provides good abrasion performance in demanding conditions.

The 330 3/16" × 1/16" HA configuration is ideal for conveying hot asphalt, oily grains, oil-treated coal, and other materials where heat and oil exposure occur together.

