



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 5-3802: 3 Ply 600 3/8 x Bare MOR

**Color:** Black

**Plies:** 3

**Nom. OAG:** 0.58" +/- 0.03"

**Fabric:** Polyester

**Top Surface:** Smooth Cover

**Top Cover Thickness:** 0.375"

**Bottom Surface:** Bare

**Compound:** MOR

**Work Tension:** 600 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.313 lbs./PIW

**Working Temp. (F):** -20 to 225

**Max. Stocked Width:** 72"

**Attributes:** Sliderbed Suitable,  
Troughable, Oil Resistant

**Hardness:** 65a

**Minimum Pulley Chart:**

Tension Rating	Min. Pulley Dia.
Over 80%	30"
60%-80%	24"
40%-60%	20"
Below 40%, tails, snubs	18"

**Features:** 5-3802 features a heavy duty, abrasion resistant top cover on a bare bottom cover. This belt can be used on a slider bed and is moderately oil resistant. 600 3/8" x Bare MOR can be used in any application requiring a heavy duty belt on a slider bed. The strong carcass is especially well-suited in the wood industry.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39