



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-3831: 3 Ply 330 1/4 x 1/16 STD

Color: Black

Plies: 3

Nom. OAG: 0.48" +/- 0.03"

Fabric: Polyester/Nylon

Top Surface: Smooth Cover

Top Cover Thickness: 0.25"

Bottom Surface: Smooth Cover

Bottom Cover Thickness: 0.0625"

Compound: SBR

Work Tension: 330 lbs./PIW

Elongation: Less than 4%

Weight: 0.26 lbs./PIW

Working Temp. (F): -20 to 250

Max. Stocked Width: 96"

Attributes: Troughable

Hardness: 65a

Minimum Pulley Chart:

Tension Rating	Min. Pulley Dia.
Over 80%	18"
60%-80%	16"
40%-60%	14"
Below 40%, tails, snubs	12"

Features: 5-3831 features a smooth top and bottom surface. The heavy cover and high strength synthetic fabric results in a long wearing, mildew and rot resistant, low stretch belt. 330 1/4 x 1/16 STD is excellent for heavy duty abrasive applications. It is used to convey gravel, rock, ore, limestone and many other industrial materials. It is also used as an elevator belt.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39