



(800) 253-6300

[sales@mulhernbelting.com](mailto:sales@mulhernbelting.com)

[www.mulhernbelting.com](http://www.mulhernbelting.com)

## 5-3833: 3 Ply 330 1/4 x 1/16 HT

**Color:** Black

**Plies:** 3

**Nom. OAG:** 0.48" +/- 0.03"

**Fabric:** Polyester/Nylon

**Top Surface:** Smooth Cover

**Bottom Surface:** Smooth Cover

**Compound:** EPDM

**Work Tension:** 330 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.26 lbs./PIW

**Minimum Pulley:** 12"

**Working Temp:** -20 to 400 °F

**Max. Stocked Width:** 72"

**Attributes:** Heat Resistant / High Temp,  
Troughable

**Hardness:** 65a

**Top Cover Thickness:** 0.25"

**Bottom Cover Thickness:** 0.063"

### Features

5-3833 is engineered for high-heat service, handling temperatures up to 350°F (fines) and 400°F (lumps). It resists cracking, hardening, and ozone damage under prolonged heat exposure.

The 330 1/4" × 1/16" HT design is well-suited for foundries, kiln-feed systems, and other severe high-temperature material handling operations.

