



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

## 5-3841: 3 Ply 600 3/8 x 1/8 STD

**Color:** Black

**Plies:** 3

**Nom. OAG:** 0.687" +/- 0.03"

**Fabric:** Polyester/Nylon

**Top Surface:** Smooth Cover

**Top Cover Thickness:** 0.375"

**Bottom Surface:** Smooth Cover

**Bottom Cover Thickness:** 0.125"

**Compound:** SBR

**Work Tension:** 600 lbs./PIW

**Elongation:** Less than 4%

**Weight:** 0.375 lbs./PIW

**Working Temp. (F):** -20 to 250

**Max. Stocked Width:** 72"

**Attributes:** Troughable

**Hardness:** 65a

**Minimum Pulley Chart:**

Tension Rating	Min. Pulley Dia.
Over 80%	30"
60%-80%	24"
40%-60%	20"
Below 40%, tails, snubs	18"

**Features:** 5-3841 features a 3 ply 600 lbs. PIW carcass and a smooth top and bottom surface. The beefy 3/8" thick top cover and high strength synthetic fabric results in a long wearing, mildew and rot resistant, low stretch belt. 3 Ply 600 3/8 x 1/8 STD is excellent for heavy duty, high weight, abrasive applications. It is used to convey gravel, rock, ore, limestone and many other industrial materials. It is also used as an elevator belt.

Warning: Trying to access array  
offset on value of type bool in  
/home/mulhernbelting/public\_html/staging.mulhernbelting.com/wp-  
content/plugins/elementor-  
pro/modules/dynamic-  
tags/tags/post-featured-image.php  
on line 39