



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-7502: 2 Ply 220 1/8 X Bare Cleated Incline MOR

Color: Black

Plies: 2

Nom. OAG: 0.45" +/- 0.03"

Recessed OAG: 0.225"

Fabric: Polyester/Nylon

Top Surface: 1/4" Chevron Profile

Top Cover Thickness: 0.125"

Bottom Surface: Bare

Compound: MOR

Work Tension: 220 lbs./PIW

Elongation: Less than 4%

Weight: 0.13 lbs./PIW

Working Temp. (F): -20 to 225

Max. Stocked Width: 72"

Attributes: Sliderbed Suitable,
Troughable, Oil Resistant

Minimum Pulley Chart:

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

Features: 5-7502 features a 1/4" high, 6" wide chevron profile in a staggered pattern. The OAG includes the profile. Use the Recessed OAG for the Lacing Recommendation. 2 Ply 1/8" x Bare Cleated Incline MOR is used in bulk conveying where oil is a concern. This is a popular specification on Diamond Z grinders and in the recycling industry.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39