



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-7531: 2 Ply 220 1/8 x 3/32 Cleated Incline - SBR

Color: Black

Plies: 2

Nom. OAG: 0.57" +/- 0.03"

Recessed OAG: 0.325"

Fabric: Polyester

Top Surface: 1/4" Chevron Profile

Top Cover Thickness: 0.125"

Bottom Surface: Smooth Cover

Bottom Cover Thickness: 0.0937"

Compound: SBR

Work Tension: 220 lbs./PIW

Elongation: Less than 4%

Weight: 0.214 lbs./PIW

Working Temp. (F): -25 to 250

Max. Stocked Width: 84"

Attributes: Troughable

Hardness: 65a

Minimum Pulley Chart:

Tension Rating	Min. Pulley Dia.
Over 80%	16"
60%-80%	14"
40%-60%	12"
Below 40%, tails, snubs	10"

Features: 5-7531 features 1/4" high, 6" wide chevron profiles in a staggered pattern. The OAG includes the profile. Use Recessed OAG for Lacing Recommendation. 220 1/8 x 3/32 Cleated Incline SBR is a popular bulk conveying belt.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39