



(800) 253-6300

sales@mulhernbelting.com

www.mulhernbelting.com

5-8532: 3 Ply 330 1/8 x 1/16 Cleated Incline - MOR

Color: Black

Plies: 3

Nom. OAG: 0.595" +/- 0.04"

Recessed OAG: 0.35"

Fabric: Polyester/Nylon

Top Surface: 1/4" Chevron Profile

Top Cover Thickness: 0.125"

Bottom Surface: Smooth Cover

Bottom Cover Thickness: 0.0625"

Compound: MOR

Work Tension: 330 lbs./PIW

Elongation: Less than 4%

Weight: 0.225 lbs./PIW

Working Temp. (F): -25 to 225

Max. Stocked Width: 72"

Attributes: Troughable, Oil Resistant

Minimum Pulley Chart:

| Tension Rating | Min. Pulley Dia. |
|-------------------------|------------------|
| Over 80% | 18" |
| 60%-80% | 16" |
| 40%-60% | 14" |
| Below 40%, tails, snubs | 12" |

Features: 5-8532 features 1/4" high, 6" wide chevron profiles in a staggered pattern. The OAG includes the profile. Use Recessed OAG for Lacing Reccomensation. This belt is popular in the wood industry and when handling oily product up an incline.

Warning: Trying to access array
offset on value of type bool in
/home/mulhernbelting/public_html/staging.mulhernbelting.com/wp-
content/plugins/elementor-
pro/modules/dynamic-
tags/tags/post-featured-image.php
on line 39