3-3713 **2 PLY PVC SAWTOOTH**











TECHNICAL DATA:

COLOR: White

NOMINAL OAG: 0.181" +/- .010

NUMBER OF PLIES: 2 ply

FABRIC: Polyester

MINIMUM PULLEY DIAMETER: 3.2"

TOP SURFACE: Sawtooth **BOTTOM SURFACE:** Bare **BOTTOM COVER:** Polyester **COMPOUND:** Oil Resistant PVC WORK TENSION: 150 lbs / PIW **ELONGATION:** Less than 2% WEIGHT P.I.W. / FT: .075 lbs

WORKING TEMPERATURE: 14F-194F

FDA ACCEPTED: Yes

JOINING METHOD: Finger Splice/Lacing

APPLICATIONS AND INDUSTRIES:

- Food Processing and Packaging
- **Bakery and Confectionery**
- Meat and Poultry Processing
- Pharmaceutical and Healthcare
- General Material Handling
- Slider bed /Pulley-Supported

FOOD GRADE



INTRODUCING: 3-3713 SAWTOOTH "The Ultimate Solution for Incline Applications"





WWW.MULHERNBELTING.COM | SALES@MULHERNBELTING.COM

☎ CONTACT US: 800 - 253 - 6300

WHY PARTNER WITH MULHERN BELTING?

WE FOCUS ON WHAT
MATTERS MOST TO
OUR VALUED PARTNERS

YOUR SUCCESS IS OUR PASSION


As a family-owned company entering our 4th generation, we cherish our heritage and the partnerships we have created over the past 91 years. With a rich history dating back to 1932, we have grown to become a global leader in the industry, proudly serving customers worldwide.

- DISTRIBUTOR DRIVEN
- DROP SHIP PROGRAM
- APPLICATION EXPERTISE
- INSTANT SUPPORT
- LARGE INVENTORY
- HIGH QUALITY MATERIALS
- ON-TIME DELIVERY

MASSIVE INVENTORY

WHATEVER YOU NEED, WE HAVE IT

CUSTOM FOOD GRADE SOLUTIONS



FROM COMPLEX DESIGNS TO SPECIALIZED APPLICATIONS MULHERN BELTING IS YOUR TRUSTED PARTNER FOR TAILOR-MADE CONVEYOR BELT SOLUTIONS.

- THERMOPLASTIC VULCANIZATION
- **OLAP SPLICES**
- FINGER/DOUBLE FINGER SPLICES
- RECESSED LACING
- PREPARED ENDS
- OHOLE PUNCHING AND PERFORATIONS
- THERMOPLASTIC PROFILES/CLEATS
- **OCUSTOM SIDEWALL**
- SKIVED SPLICES



WWW.MULHERNBELTING.COM | SALES@MULHERNBELTING.COM

CONTACT US: 800 - 253 - 6300